

ULIN-CH02PC

Technical Datasheet



Features

- Specifically designed to charge Ultralife UBI-2590 (UBBL02,UBBL10 and UBBL13) batteries safely & efficiently
- LED status indicator
- Safety circuit protects against charging shorted battery packs
- Contains charger, universal power supply and line cord

Applications

- Charger for UBI-2590 battery family

Technical Specifications	
Part No.	ULIN-CH02PC
DC Input	19-24VDC
DC Output	16.8 V Dual Output (2 channel)
Charge Rate	1.7A per channel
Battery Types	Li-Ion
User Interface	LED Amber ON : Power up LED Yellow ON : Charging LED Red ON : Error LED Green ON : Fully charged
Connectors	Input: 2.5mm Pin DC Socket Output: Panel Mount Connector
Color	Black
Finish	Case Material: Aluminium
Size	Charger: 183mm (7.2in) x 101mm (3.97in) x 40mm (1.57in)
Weight	430 gms
Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 60°C
Accessories Included	Power Supply - ADP-90DD B Input Voltage: 100-240VAC, 50-60Hz Weight: 405 gms AC Power Cord Options: North America: 1090-01-0002 AUS: 1090-01-0004 EUR: 1090-01-0008 IND: 3 PIN TYPE D